

SECURE ACCESS

Cargo doors, locking gear and seals support controlled access and weather resistance.

DURABLE STEEL BODY

Built for hard use; construction, finish and included equipment vary by model.

FLOOR & HANDLING

Durable cargo floor with handling provisions where supplied by the manufacturer.

WEIGHT & DIMENSIONS

EXTERIOR	20FT L x 8FT W x 8FT 6IN H
INTERIOR	Approx. 19FT 4IN L x 7FT 8IN W x 7FT 10IN H
DOOR / ACCESS	Cargo doors at both ends
TYPICAL TARE	Manufacturer-specific
TYPICAL PAYLOAD	Manufacturer-specific



MODEL ADVANTAGE

Cargo access at both ends supports long materials, first-in/first-out inventory and divided storage zones without unloading everything in front.

VENTILATION / SEALS

Weather-resistant vents and gaskets help manage ordinary dry-storage conditions.

DERKSON SUPPORT

Compare live units, plan delivery and add accessories or modifications in one process.

WHY THIS MODEL

Cargo access at both ends supports long materials, first-in/first-out inventory and divided storage zones without unloading everything in front.

MODIFICATION OPTIONS

PAINT & DECALS	ROLL-UP DOORS	PERSONNEL DOORS
WINDOWS	INSULATION	ELECTRICAL

ACCESSORIES

LOCKBOXES	PADLOCKS	VENTS
SHELVING	STACKING HARDWARE	DECK MOUNTS