

SECURE ACCESS

Cargo doors, locking gear and seals support controlled access and weather resistance.

DURABLE STEEL BODY

Built for hard use; construction, finish and included equipment vary by model.

FLOOR & HANDLING

Durable cargo floor with handling provisions where supplied by the manufacturer.



MODEL ADVANTAGE

Wide side access makes bulky material, event equipment and fast loading easier than an end-door-only container, while the steel shell remains secure when closed.

VENTILATION / SEALS

Weather-resistant vents and gaskets help manage ordinary dry-storage conditions.

DERKSON SUPPORT

Compare live units, plan delivery and add accessories or modifications in one process.

WEIGHT & DIMENSIONS

EXTERIOR	20FT L x 8FT W x 8FT 6IN H
INTERIOR	Approx. 19FT 4IN L x 7FT 6IN W x 7FT 6IN H
DOOR / ACCESS	End approx. 7FT 3IN W x 7FT 2IN H; side approx. 19FT 2IN L x 7FT 2IN H
TYPICAL TARE	Approx. 7,010 lb

TYPICAL PAYLOAD Approx. 60,190 lb

WHY THIS MODEL

Wide side access makes bulky material, event equipment and fast loading easier than an end-door-only container, while the steel shell remains secure when closed.

MODIFICATION OPTIONS

PAINT & DECALS	ROLL-UP DOORS	PERSONNEL DOORS
WINDOWS	INSULATION	ELECTRICAL

ACCESSORIES

LOCKBOXES	PADLOCKS	VENTS
SHELVING	STACKING HARDWARE	DECK MOUNTS