

SECURE ACCESS

Cargo doors, locking gear and seals support controlled access and weather resistance.

DURABLE STEEL BODY

Built for hard use; construction, finish and included equipment vary by model.

FLOOR & HANDLING

Durable cargo floor with handling provisions where supplied by the manufacturer.



MODEL ADVANTAGE

Insulated, powered temperature-control storage for compatible cold-chain, food, beverage and commercial applications. Confirm electrical service, machinery condition and operating range for the selected unit.

VENTILATION / SEALS

Weather-resistant vents and gaskets help manage ordinary dry-storage conditions.

DERKSON SUPPORT

Compare live units, plan delivery and add accessories or modifications in one process.

WEIGHT & DIMENSIONS

EXTERIOR	Approx. 40FT L x 8FT W x 9FT 6IN H
INTERIOR	Unit-specific due to insulation and machinery
DOOR / ACCESS	Reefer cargo-door opening; unit-specific
TYPICAL TARE	Unit-specific

TYPICAL PAYLOAD Unit-specific

WHY THIS MODEL

Insulated, powered temperature-control storage for compatible cold-chain, food, beverage and commercial applications. Confirm electrical service, machinery condition and operating range for the selected unit.

MODIFICATION OPTIONS

PAINT & DECALS	ROLL-UP DOORS	PERSONNEL DOORS
WINDOWS	INSULATION	ELECTRICAL

ACCESSORIES

LOCKBOXES	PADLOCKS	VENTS
SHELVING	STACKING HARDWARE	DECK MOUNTS